

## What is Grab?

GRAB is an effective, low odour product that dissolves ink and paint graffiti from any surface subject to graffiti.

## How Does It Work?

GRAB is a very powerful solvent-type paint and ink removal agent. It is water-emulsifiable so it can be rinsed away effectively with water. It is a low odour liquid with outstanding performance and it is a thickened liquid so it will "cling" to vertical surfaces. GRAB will not leave unwanted chemical odours after being used. It is classified as Dangerous Goods.

### For Use On...

GRAB quickly and thoroughly dissolves aerosol paint, felt-tipped pen ink, ballpoint pen ink and other graffiti from stone, fibreglass, concrete and brickwork. It is ideal for use on walls and brickwork, and other surfaces subjected to graffiti. It should not be used on painted surfaces or aluminium metal.

### Caution

Use caution before applying GRAB to soft vinyl or plastic. It is advisable to pre-test the product on unknown or sensitive surfaces to ensure no damage will occur. Avoid spilling the product on paintwork, shoes and furniture. Wear solvent-resistant gloves (nitrile or neoprene) to prevent skin contact. Do not leave the product lying around after use. Also, avoid using food containers for storing the product. Read the MSDS for GRAB and observe all safety precautions.

## Technical Data

### Properties



COLOUR – Transparent brown liquid

ODOUR – Orange citrus

pH = >13

VISCOSITY – Slightly 'thick' liquid

### Dangerous Goods Classification:

GRAB is a Class 3 flammable and Class 8 Corrosive Liquid.

UN No.: 2924	CLASS: 3, 8
PACK GRP: III	HAZCHEM: 3W

### Environmental Care



GRAB conforms with all statutory environmental requirements. It is based on powerful ingredients selected to perform efficiently so there is no waste or damage. GRAB containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

### Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements".

First Certified: 30 April 1996

SAI Certificate No.: QEC7358

## Application

- Graffiti is easiest to remove when it is fresh.
- GRAB is not suitable for use on aluminium or painted surfaces because it will strip the paint. To remove graffiti from painted walls or aluminium surfaces, use DLX.
- **Metal, Fibreglass, Tiles, Glass**
  1. Wear gloves and safety glasses when using this product.
  2. Brush GRAB onto the graffiti. Apply a thick uniform film. Do not apply to aluminium.
  3. Scrub for a minute with a brush to assist penetration. Smooth over then leave to work for 5 minutes.
  4. Scrub the graffiti with a brush or a nylon scourer.
  5. Wipe the graffiti off with a rag, or rinse off with a hose.
  6. If any graffiti is left, repeat steps 1 to 4.
  7. Wash over all areas with clean water.
- **Concrete or Brick**
  1. Use a stiff nylon or wire brush.
  2. Follow steps 1 to 4 above.
  3. Brush over all treated areas then rinse with clean water.

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.