

Drain systems are used primarily for grease trap maintenance but are suitable for many applications where intermittent timed dosing operations are needed. The Drain systems automatically meter exact amounts of chemical anytime of the day or night as desired, without waste.



### TECHNICAL CHARACTERISTICS

- **CERTIFICATIONS**
  - CE, EAC
- **ELECTRICAL CLASS**
  - Class II (ground connection not needed)
- **FLOW RATES**
  - Fixed at 7 l/h
- **BACK PRESSURE**
  - Up to 1 bar
- **POWER SUPPLY**
  - 100-240Vac @50/60 Hz - 5 W
- **MATERIALS**
  - **ENCLOSURE:** PP with fiber glass
  - **PUMP HEAD:** PP with talcum
  - **TUBE:** Santoprene
- **DOSING**
  - Intermittent dosage at maximum speed
  - Maximum 1 feed per hour
- **PROTECTION RATE**
  - IP65
- **ENVIRONMENTAL OPERATING TEMPERATURE**
  - 5-50°C
- **STORAGE TEMPERATURE**
  - -20-60°C
- **MOTORS**
  - Brushed DC Motors
- **INSTALLATION KIT/ACCESSORIES**
  - Installation kit with wall bracket and fixing screws
  - PVC suction and delivery tube
  - FPM Lip seal check valve

### FEATURES

- **IP65** Protection degree and class II electrical insulation
- Easy and quick installation and programming
- Digital interface with 4 digits 7 segments display and 2 keys
- IP 65 Protection degree
- Transaxle technology for extended motor life
- Switch with 3 position, ON, Priming, Stand By
- Password protection for programming
- Possibility to set dosage start at selected intervals (max 1 per hour) for a predetermined time.

### DIMENSIONS

